

TRUNK CABLES DE COBRE - FICHA TÉCNICA

Publicado en 30-07-2025 por barpaadminuser





COPPER TRUNK CABLES

DESCRIPTION

barpa's Copper Trunk Cables are preterminated solutions ideal for rack-to-rack mirroring, especially in high-density environments such as data centers.

Designed to optimize organization and accelerate the deployment of multiple structured links, they are manufactured and tested at our Internal Production Unit (Higgs), ensuring consistent performance, quality assurance, and full compliance with international standards.











STANDARDS

- ISO/IEC 11801 EN 50173 ANSI/TIA-568.2-D EN 50575 (CPR)
- Directive 2011/65/EU (RoHS)

FEATURES

100% tested for electrical performance (Permanent Link / Channel / MPTL)

Available in shielded (STP) or unshielded (UTP) options

CPR-rated cables (Dca, Cca, B2ca)

Fully compliant with performance requirements of Cat6, Cat6A, and Cat8 categories

Supports PoE, PoE+ and 4PPoE

Different Lengths and Bundles Available: performance guaranteed up to 90 m in accordance with EN 50173, ISO/IEC 11801-1 and ANSI/TIA-568.2-D

Supplied with Fluke Test Report to ensure quality and performance

Each cable is uniquely labeled with a QR Code for full traceability

Country of Origin: Portugal

This document is authored and owned by loops. It is forbidden to reproduce in whole or in part without mentioning its authorable, as well as modification of its content or context. A specifications are well-set to drange without notice.

The picture directings one metryl instant true.

datasheet n° b195_0 | date: 07/25

